

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The following diesel or incomplete medium-duty vehicles (MDV) with a manufacturer's GVWR from 8501 to 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	EXECUTIVE ORDER			NGINE	EMISSION	FUEL TYPE 1 STANDAR		ENGINE		OBD
			MANU	FACTURER	STD CATEGORY 2	Diesel	& TEST PROCEDURE	SIZES (L)	ECS & SPECIAL FEATURES 3 ECM, OC, EGR, DDI, TC, CAC	OBD(F)
				AL MOTORS	CATEGORY					
2005			COR	PORATION	ULEV		Diesel	6.6		
				The second of the second of the second	10.7	V I	EHICLE DESCRIP	TION	Contract to the second	
EVAPORATI FAMILY		UL (K)	FUEL TANK CAPACITY (gallons)	VEHICLE MODEL YEAR	VEHIC	LE MAKE & MODEL	S	ENGINE (L)	ENGINE MODELS / CODES (rated power, in hp)	OBD COMPL ANCE
•		•	•	2005	AM (AM General Hummer H1			LLY / 1 (310), LLY / 51 (310), LLY / 61 (300), LLY / 71 (300)	OBD(F)
*		•	•	•		•			•	•
		1 * 1	•							
										

anot applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 88.abc=Title 40, Cade of Federal Regulations, Section 86.abc; [2004msy26]

L=tier; np=norsepower; kw=kirowar;

CNG/LNG=compressed/liquefied natural gas; LPG=tiquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a BF=bi fuel; DF=dual fuel; FF=flexible fuel;

SULEV / ULEV / LEV=super uitra / uitra / low emission vehicle;

SULEY / ULEY / LEY = super urra / urra / low emission venice;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) = warm-up catalyst; DPF=diesel particulate filter; HO28/O28=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCAR8=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke pulf limiter; OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For dual- and flexible-fuel, the CERT values in brackets [] are those when tested on conventional test fuel.)

NMHC		NOx		NMHC+NOx		CO		PM		нсно	
FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
0.5	0.5	•	•	2.5	2.5	14.4	14.4	0.10	0.10	0.050	0.050
•	*	•	•	. •		•	•		1		
0.2	0.1	•	•	2.4	2.1	2.0	0.2	0.08	0.07	0.022	0.005
0.625			•	3.125		18.0		0.125		0.0625	
	0.5 *	FTP EURO 0.5 0.5 0.2 0.1	FTP EURO FTP 0.5 0.5 * 0.2 0.1 *	FTP EURO FTP EURO 0.5 0.5 * * * * * * 0.2 0.1 * *	FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 * * * * * 0.2 0.1 * * 2.4	FTP EURO FTP EURO FTP EURO 0.5 0.5 * * 2.5 2.5 * * * * * * 0.2 0.1 * * 2.4 2.1	FTP EURO FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 2.5 14.4 * * * * * * * 0.2 0.1 * 2.4 2.1 2.0	FTP EURO FTP EURO FTP EURO FTP EURO 0.5 0.5 * * 2.5 2.5 14.4 14.4 * * * * * * * * 0.2 0.1 * * 2.4 2.1 2.0 0.2	FTP EURO FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 2.5 14.4 14.4 0.10 * * * * * * * * * 0.2 0.1 * 2.4 2.1 2.0 0.2 0.08	FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO 0.5 0.5 * * 2.5 2.5 14.4 14.4 0.10 0.10 * * * * * * * * * 0.2 0.1 * 2.4 2.1 2.0 0.2 0.08 0.07	FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 2.5 14.4 14.4 0.10 0.10 0.050 *

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the optional emission standards and test procedures in 13 CCR 1956.8 applicable to diesel or incomplete MDV with a 8501-14000 pound GVWR and shall be subject to 13 CCR 2139(c) (in-use testing of engines certified for use in diesel or incomplete MDV with a 8501-14000 pound GVWR).

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1968.2 (on-board diagnostic, full or partial compliance), 13 CCR 1976(b)(1)(B)-(C) or 13 CCR 1976(b)(1)(F) {evaporative emission standards}, 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle fuel tanks]. (The braces {} are for gasoline, LPG or alcohol fueled vehicles only.)

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

ZTH

Executed at El Monte, California on this

_ day of September 2004.

Allen Lyons, Chief Mobile Source Operations Division